INOX | Upright Cabinets

REFRIGERATED CABINETS ► GN2/1-NO FROST ► CHILLER

11111111

1111111

Plastic thermal-braker anti-condensation as chamber body frame





QR 6-5A



















DETAILS







Inverter





Evaporator with anti-corrosion treatment



Inner stainless steel waved guides



Anti-condensation door frame



Lock fitted as



Digital control and white backlit main switch

2045

850



Inner LED light



Cabinet suitable for GN2/1 pans

TECHNICAL SPECIFICATIONS

GENERAL FEATURES

Ventilated Cooling Inverter compressor

Digital Thermostat White backlit main switch

Removable Gasket

Foamed door handle

Stainless Steel exterior and interior

Evaporator with anti-corrosion treatment Automatic defrost with electric heater

Foaming Agent Cyclopentane (80mm)

LED light and lock fitted as standard

Door: Self closing and reversible door fitted as standard

N.4 S/S Adjustable feet - (Lockable castor as Optional)

Curved edge for easy cleaning

<u>Adjustable shelves GN2/1: 3</u> + 1

Energy efficiency class: A

GN2/1 Refrigerated upright cabinet (CLASS A)

Capacity	546 L
Temperature	-2° ~ +8°C
Consumption	0.723 kWh/24h
Rated Power	73 W
Noise level	58 dB(A)
Net Weight	109.00 Kg
Gross Weight	122.00 Kg
External Dimensions (WxDxH mm)	700x850x2045
Internal Dimensions (WxDxH mm)	534x685x1485
Packaging dimensions (WxDxH mm)	720x870x2110
Loading quantities 20'/40'/40'HQ	21/42/42

CERTIFICATION

(E C



RoHS





PRODUCT DIMENSIONS

ů

700

⊉75